

TOOLS NEEDED:
4MM ALLEN
1/4" ALLEN



HARDWARE NEEDED:
504286, Joint Conn. Bolt 1/4-20 x .591
504290, Joint Conn Nut 1/4-20 x .275
503529, Clip, Panel Bracket

QTY - 4 OF EACH



Clips will be positioned as shown- capturing the wires against the panel. Joint Conn Bolt will pass through bracket and thread into the Joint Conn Nut.



PANEL SHOULD BE CENTERED AS SHOWN ABOVE

REV	DESCRIPTION	DATE
01	INITIAL RELEASE	06/28/2018

GEARGRID		NAME	DATE	TITLE:	
DRAWN: Luke B.		ENGINEER	07/17/2026	ACM, Foot Locker Panel Install	
PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF GEARGRID CORPORATION. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF GEARGRID CORPORATION IS PROHIBITED.		UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN INCHES TOLERANCES: ANGLE MACHINED ±.5° ANGLE FORMED ±1° TWO PLACE .XX THREE PLACE .XXX HOLE Ø ±.010 ±.005		SIZE	PART NO.
INTERPRET DIM AND TOLERANCE PER ASME Y14.5M-1994		THIRD ANGLE PROJECTION		D	800095-5
FINISH		REV		02	
DO NOT SCALE DRAWING		SHEET 1 OF 1			